Product data sheet Characteristics

QO140L200PGRB

Load center, QO, 1 phase, 40 spaces, 60 circuits, 200A convertible main lugs, PoN, NEMA3R, gnd bar, UL





Main

QO
Load Center
Weatherproof enclosure
Grounding bar

Complementary

Complementary		
PoN Convertible Mains (lugs)	PoN Convertible Mains (lugs)	
Rated Current	200 A	
Number of Spaces	40	
Max Short Circuit Current Rating	65 kA	
Maximum Number of Single Pole Circuits	40	
Maximum Number of Tandem Breakers	20	
Number of Phases	1 phase	
Ground Bar	Grounding bar included (not installed)	
Box Number	7R	
Height	33.78 in (858 mm)	
Width	14.76 in (375 mm)	
Depth	4.53 in (115 mm)	
Net Weight	39.90 lb(US) (18.100 kg)	

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	10002-QO PON 1PH LC,12-60 CKT, N3R
Discount Schedule	DE3A
GTIN	785901086093
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.53 in (11.5 cm)
Package 1 Width	14.76 in (37.5 cm)
Package 1 Length	33.78 in (85.8 cm)
Package 1 Weight	38.45 lb(US) (17.441 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations