

made in italy - globally renowned

IT'S ALL IN THE NAME 7 I L - K I T

7ILMET

THE ALL NEW Boiler Trim Kit Package.

THIS ENABLES THE INSTALLER TO CARRY THE ESSENTIAL COMPONENTS FOR A HEATING SYSTEM IN 1 COMPACT UNIT.

The assembly includes the following quality components, air separator, boiler fill valve, multi-isolation valve and a backflow prevention device all of which help to provide a quick and efficient installation process.

- NPT or SWT connections
- All-in-one package solution
- Multi-Isolation Valve
- Drain off outlet for ease of system servicing
- Microbubble Deaerator
- 4.8 Gallon heating vessel

WWW.ZILMETUSA.COM T. (401) 884 4943



TECHNICAL SPECIFICATION:

BOILER FILL VALVE: ZU0007

Max Operating Pressure: 150 PSI Max Operating Temperature: 230°F Adjustment Range: 7.5 - 100 PSI Pressure Gauge Scale: 0 - 58 PSI Usable Fluid: Water Connections: 1/2" NPT

BACKFLOW PREVENTER: ZU0008/ZU0009

Max Operating Pressure: 175 PSI Working Temperature: 32-210°F Usable Fluid: Water Approvals: ASSE 1012, CSA B64.3 Connections: 1/2" NPT / SWT

MICROBUBBLE DEAERATOR: ZU0001/2/3/4/5/6

Max Operating Pressure: 150 PSI Max Operating Temperature: 230°F Max Discharge Pressure: 150 PSI Usable Fluid: Water Inlet Connections: 3/4", 1", 1 1/4" NPT/SWT Bottom Connection: 1/2" NPT AISI 304 Stainless Steel Filter

MULTI ISOLATION VALVE: ZU0020


Max Operating Pressure: 150 PSI Usable Fluid: Water Connections: 1/2" NPT


BRASS CONNECTOR NIPPLE: ZU0010


Connection: 1/2" NPT

HEATING VESSEL: ZHT18

Capacity: 4.8 gallon Max Operating Pressure: 60 PSI Max Operating Temperature: 210°F Precharge: 12 PSI Usable Fluid: Water Connection: 1/2" NPT *Max Glycol for all parts is at 50*%



















WWW.ZILMETUSA.COM