



U1234-RXL-KK-K1

4 Terminal Ringless Large Hub Open Adapt To Small Closing Plate Horn Bypass 4 Position Single Connector 6-350kcmil

SPECIFICATIONS



Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	300 Volts Alternating Current
Amperage Rating	150 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.125L x 42.688W x 16H
Number of Main Breakers	0
Main Breaker Size	No Main Breaker
Cable Entry	Overhead or Underground
Terminal	Single Mechanical
Insulation	Glass Polyester
Mounting	Surface Mount
Material	G90 Galvanized Steel with Powder Coat Finish
Number of Jaws	4 Terminal
Bypass Provision	Horn Bypass
Number of Meter Positions	4 Positions
Equipment Ground	Triplex Ground
Hub/Closing Plate	Large Hub Opening Adapted to Small Hub Opening
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0
Height	16 IN
Length	5.125 IN
Width	42.688 IN

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply

with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.