


Insulation Jacketing Tape



Backing: **Embossed PVC Film**

Adhesive: Acrylic

Liner: **Paper**

Colors: White

Specifications: N/A

Standard Sizes: 3" x 50Yd

Applications

Seaming and patching vinyl-faced fiberglass • Maintaing vapor barrier integrity for water insulation materials.

heater insulation blankets.

Features Benefits

Embossed PVC Film	 Conformable and durable 	
	 Excellent moisture barrier properties 	
 Acrylic Adhesive 	 Provides a strong long-term bond 	
	 No flagging or lifting 	
	 Excellent all-temperature performance 	

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	4.6 mils	0.117 mm	ASTM D-1000
Adhesion to Steel	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	7 lb/in	12.26 N/cm	ASTM D-1000
Elongation	100%		
Operating Temperature	-40 to 225 °F	-40 to 107 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.