
# **POLYKEN®**



## **Premium Grade Duct Tape**



Backing: PE Coated Cloth

Adhesive: Rubber Liner: N/A

Colors: Silver, Black, White

**Specifications:** Tested in accordance with UL 723

**Standard Sizes:** 48mm x 55m, 72mm x 55m

#### **Applications**

- Waterproof repairs
- Heavy-duty packaging and bundling
- Seaming and securing underlayment
- Plastering applications

- Heavy-duty contractor and manufacturing uses
- Mediablast protection
- Seaming and sealing for heavy PE sheeting and tarps

#### Features Benefits

PE-Coated Cloth Backing	<ul> <li>High tensile strength for difficult applications</li> <li>Puncture &amp; abrasion resistance</li> <li>Crisp, straight tear</li> <li>Moisture, solvent &amp; abrasion resistant</li> </ul>
<ul> <li>Natural Rubber Based Adhesive</li> </ul>	<ul> <li>Aggressive adhesion to all surfaces including concrete and other rough textures</li> </ul>
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>

### **Typical Test Values**

	Standard UOM	Metric UOM	Test Method	
Total Thickness	13.0 mils	0.330 mm	ASTM D-1000	
Adhesion to Steel	95 oz/in	10.39 N/cm	PSTC-101	
Tensile Strength	50 lb/in	87.56 N/cm	ASTM D-1000	
Elongation	13%		ASTM D-1000	
Smoke Developed	20		UL 723	
Flame Spread	15		UL 723	
Operating Temperature	40 to 200 °F	4 to 93 °C		
VOC Content	<1 g/L			

Recommended Storage Conditions: 32-90 °F at 50% RH  $\pm$  2% Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

