For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

1-12DE/ 1-20DE/ 1-30DE/ 3-12DE Copper Toilet Riser w/ Heavy Duty Rubber Nosepiece

Use: For use in potable water distribution systems in accessible locations only.

Design Features:

- One-piece construction
- Cut to Length for professional finished appearance

Operating Specifications:

Temperature: 40°-180° F

Pressure: 125 psi maximum

Tubing Diameter: 0.38" O.D. or 0.50" O.D.


MATERIAL SPECIFICATIONS				
Tube	C12200 copper per ASTM B-68			
Nosepiece Support	POM			
Washer	EPDM rubber			



Part Listing:

1-12DE C	3/8" OD Tube x 11-1/2" Length, chrome plated
1-12DE CBT	3/8" OD Tube x 11-1/2" Length, chrome plated, plain label, bulk
1-12DE-1 R	3/8" OD Tube x 11-1/2" Length, no washer, rough finish
1-12DE BZP	3/8" OD Tube x 11-1/2" Length, oil rubbed bronze, bagged
1-12DE NSP	3/8" OD Tube x 11-1/2" Length, satin nickel, bagged
1-20DE C	3/8" OD Tube x 19-1/2" Length, chrome plated
1-20DE CBT	3/8" OD Tube x 19-1/2" Length, chrome plated, plain label, bulk
1-20DE-1 R	3/8" OD Tube x 19-1/2" Length, no washer, rough finish
1-20DE BZP	3/8" OD Tube x 19-1/2" Length, oil rubbed bronze, bagged
1-20DE NSP	3/8" OD Tube x 19-1/2" Length, satin nickel, bagged
1-30DE C	3/8" OD Tube x 29-1/2" Length, chrome plated
2-12DE C	1/2" OD Tuho v 11-1/2" Langth, chrome plated

1-12DE/ 1-20DE/ 1-30DE/ 3-12DE Copper Toilet Riser w/ Heavy Duty Rubber Nosepiece



PART DIMENSIONS (Inches)				
Model	DIM. A	DIA. B		
1-12DE	11.56	3/8		
1-20DE	19.56	3/8		

PART DIMENSIONS (Inches)					
Model	DIM. A	DIA. B			
1-30DE	29.56	3/8			
3-12DE	11.56	1/2			

Listings & Certifications:

IAPMO listed to ASME A112.18.1-2005 / CSA B125.1-2005 (File # 0645)



