For Residential and Commercial Applications			
Job Name	Engineer / Architect		
Job Location	Wholesaler		
Submittal Date	Contractor		

B1-**KC Speedi Plumb® PLUS Braided Faucet Connectors - Compression Inlet x KC Nosepiece Outlet

Use: For use in potable water distribution systems in accessible locations only.

Design Features:

- Engineered polymer braided fibers bend freely without kinking or crimping
- Reinforced PVC inner hose ensures durability
- Rubber washers provide a large pliable sealing surface and ensure a long lasting water-tight connection
- 8-sided pneumatic crimp provides greater dependability for reliable nut-to-hose connections
- . Ø No Lead

Operating Specifications:

Temperature: 40°-140° F, intermittent to 180° F

Pressure: 125 PSI maximum


Tubing Diameter: 0.300" ID (0.550" OD)




MATERIAL SPECIFICATIONS				
Inner Hose	Reinforced PVC			
Braiding	PVC coated polyester yarn			
Barb	Brass			
Ferrule	Zinc-plated steel			
Washer	Rubber			
Compression Ring	Brass			
Compression Nut	Brass, chrome plated			
KC Barb	Compliant brass, chrome plated			

Part Listing:

B1-12KC F	3/8" compression x 3/8" OD compression x 12" length
B1-16KC F	3/8" compression x 3/8" OD compression x 16" length
B1-20KC F	3/8" compression x 3/8" OD compression x 20" length



B1-KC Speedi Plumb® PLUS Braided Faucet Connectors - Compression Inlet x KC Nosepiece Outlet



PART DIMENSIONS (Inches)		
Model	DIM. A	
B1-12KC	12.0 / 13.0	
B1-16KC	16.0 / 17.0	
B1-20KC	20.0 / 21.0	

Listings & Certifications:

- IAPMO listed to ASME A112.18.6 and CSA B125.6 (File # 0452)
- CSA listed to ASME A112.18.6 and CSA B125.6 (File #204593)
- No-Lead product CSA listed to Low-Lead Content Certification Program – Plumbing Products Class 6853-01







