

Product Specifications

Construction

- Diecast aluminum housing and heatsink for durability
- Polycarbonate lens seals LED for IP65 rating
- Impact protection rating IK08 Lens and IK08 Housing

Electrical

- Long-life LED system with electronic driver for optimal performance
- Selectable power switch for 3 levels of lumen output per model
- Selectable color switch provides 4000 or 5000K CCT at CRI >82
- Multi-volt 120 through 347V operation
- 0-10V dimming, 10% standard
- 7ft (86") long power and dimming cord provided for easier installation
- Integral 4K surge protector
- Operating temperature of -40°C to 50°C
- Default CCT/Lumen setting is 4000K and High Power

Optics

- Medium distribution standard

Mounting

- Mounting hook included
- Designed for suspension mounting with 1/2" threaded hub
- Available ADAPTHUB accessory for 3/4" NPS threaded stem

Compliance

- cULus listed for wet location
- NEMA 4X, IP65 rated
- NSF/ANSI standard 2 - Light fixture for Splash Zone and Non-Food Zone rated luminaire models.
- IESNA LM-79 and LM-80 standards compliant
- Qualifies as State of California Title 24 non-residential high efficiency luminaire
- FCC part 15 class A compliant
- DesignLights Consortium® Qualified and classified for DLC Premium, refer to www.designlights.org for details.

Sensor

- Plug and play low-voltage sensor accessory available
- Sensor installs directly to integral fixture port
- PIR motion sensor with 0-10V control
- Wet location and IP65 rated
- Up to 50ft mounting height
- Sensor remote control must be ordered separately

Emergency Pack Option

- 120-347V universal input remote emergency driver accessory available
- Field installed EM driver wires directly to fixture
- 90-minute batteries provide constant power to the LED system
- Test switch/indicator button can be tested safely from the ground using remote control
- EM remote control included with accessory
- Accessory comes with grommets and mounting hardware, see EM driver spec sheet.

Finish

- White or black polyester powder coat finish painted after fabrication

Warranty

- Five year limited warranty

Accessories List

| Catalog Number | Description | Unit Carton UPC |
|-------------------------------|--|-----------------|
| UHBS-SMB | UHBS Surf Mnt Brkt for 13"/15" Model | 080083273263 |
| UHBS-SMB-BLK | UHBS Surf Mnt Black Finish | coming soon |
| UHBS-CLR13 | UHBS 13 Clear PC Reflector | 080083273300 |
| UHBS-CLR15 | UHBS 15 Clear PC Reflector | 080083273317 |
| UHBS-ALR13 | UHBS 13 Aluminum Reflector | 080083273324 |
| UHBS-ALR15 | UHBS 15 Aluminum Reflector | 080083273331 |
| UHBS-WG13 ⁽²⁾ | UHBS 13 dia. Wire Guard | 080083273348 |
| UHBS-WG15 ⁽²⁾ | UHBS 15 dia. Wire Guard | 080083273355 |
| UHBS-CDL13 ⁽³⁾ | UHBS 13 Clear Lens Cover & Clamp | 080083273362 |
| UHBS-CDL15 ⁽³⁾ | UHBS 15 Clear Lens Cover & Clamp | 080083273379 |
| EBP-RM40R ⁽⁶⁾ | 40W Emergency Driver, Remote Mount 120-347V White w/ remote included | 080083259496 |
| UHBS-SENSOR PK ⁽⁶⁾ | PIR Sensor 360 Lens 60FT MH Kit | 080083257898 |
| UHBS SENSOR REMOTE | UHBS Sensor Remote Control | 080083260249 |
| UHBS-ADAPHUB ⁽⁴⁾ | UHBS Adapter HUB-3/4NPS | 080083259830 |
| UHBS-ADAPHUB-BLK | UHBS Adapter Hub Black Finish | coming soon |
| UHBS-SC7 ⁽⁵⁾ | UHBS Safety Cable 7FT long with Clip | 080083259854 |
| UHBS RING | UHBS Ring Mount Accessory | 080083260225 |

Notes: (2) Installs directly to fixture only. (3) Fits onto clear PC reflector only. Do not attach directly to the fixture. (4) Rigid mount not for use in gymnasiums. (5) The Safety Cable accessory shall be utilized only as a secondary safety and not the primary means of mounting. (6) To meet state and local codes, EBP cannot be used with UHBS with sensor or with UHBS sensor accessory. (7) Also available in black finish.



ALR
Aluminum Reflector




CLR
Clear Reflector



CDL
Clear Lens Cover



WG
Wireguard



SMB⁽⁷⁾
Surface Mount Bracket



ADAPHUB⁽⁷⁾
3/4 NPS Hub adapter



SENSOR⁽⁶⁾
Plug in sensor



EBP-RM40R⁽⁶⁾
Field installed Remote EM