



SR SERIES COUPLINGS

Shear Resistance & Flexibility



SR Series Standard
Shear Banded
Couplings



- 300 SS worm gear clamps
- 4 Banded Coupling

SR Series SPECIFICATIONS

SR– Dallas Specialty Standard Shear Banded Couplings are designed for such applications as under driveways and load bearing conditions where shear forces exist. Reduced size couplings assembled with molded bushings. For Underground Piping Systems.

Gasket

- Manufactured in the USA meeting material requirements of:
IPC/IRC® cUPC®
ASTM C-1173
- Non-Phthalate Resins
- Flexible PVC

Clamp / Shield

- All Stainless Heavy Duty Shield .012 Thickness
- 1/2" width band
- 5/16" worm gear screw
- 60# Torque

DS Gasket Material Exceeds ASTM C-1173 Specification

Compound Specs for DS Gaskets/Coupling Material

Typical Properties	C-1173 spec	DS/605-60	ASTM#
Durometer Shore A, ±3 15sec	50-75	60	D-2240
Tensile Strength, PSI	1000	1525	D-412
Ultimate Elongation, %	200	363	D-412
Brittle Temperature Tb °C	-40	-40	D-746
Tear Strength	150" lb	150" lb	D-746
PHthalates FREE COMPOUND			



DALLAS SPECIALTY & MFG. CO.
1161 RUGGLES ST GRAND PRAIRIE, TX 75050
972-641-8444 * 1-800-222-5644 * fax 972-641-8488
www.dallasspecialty.com