

# Product data sheet

Specifications

**SQUARE D**



## Safety switch, heavy duty, fused, viewing window, Type 1, 240V, 30A, 3 pole, neutral installed

VH321N

### Main

<b>Product</b>	Single Throw Safety Switch
<b>Duty Rating</b>	Heavy duty
<b>Device Application</b>	Heavy application
<b>Disconnect Type</b>	Fusible disconnect
<b>Factory Installed Neutral</b>	Neutral (factory installed)
<b>Number of Poles</b>	3
<b>Current Rating</b>	30 A
<b>Voltage Rating</b>	250 V DC 240 V AC
<b>Enclosure Rating</b>	NEMA 1 steel
<b>Motor power hp</b>	1.5 hp at 240 V AC 50-60 Hz for 1 phase motors 3 hp at 240 V AC 50-60 Hz for 3 phase motors 3 hp at 240 V AC 50-60 Hz for 1 phase motors 7.5 hp at 240 V AC 50-60 Hz for 3 phase motors 5 hp at 250 V DC

### Complementary

<b>Short-circuit current</b>	10 kA for H, K, J or R without fuse rejection clips 200 kA for R with fuse rejection clips 200 kA for J
<b>Fuse type</b>	H or K R or J
<b>Mounting Type</b>	Surface
<b>Electrical Connection</b>	Lugs
<b>Wiring configuration</b>	4-wire (3PH + N)
<b>Wire Size</b>	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
<b>Tightening torque</b>	45 lbf.in (5.08 N.m) 0.02 in <sup>2</sup> (13.3 mm <sup>2</sup> ) (AWG 6) 40 lbf.in (4.52 N.m) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) (AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) (AWG 14...AWG 10)
<b>Depth</b>	5.11 in (129.79 mm)
<b>Width</b>	6.36 in (161.54 mm)
<b>Height</b>	14.57 in (370.08 mm)
<b>Product Weight</b>	8.82 lb(US) (4 kg)

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Grounding Kit</b>	Field installed kit available
<b>Service Entrance</b>	Suitable service entrancefor USA Suitable service entrancefor Mexico

## Environment

<b>Certifications</b>	UL listed file E2875
-----------------------	----------------------

## Ordering and shipping details

<b>Category</b>	00008-H&HU SW,2&3P,N1,30-200A
<b>Discount Schedule</b>	DE1
<b>GTIN</b>	3606485893365
<b>Returnability</b>	Yes
<b>Country of origin</b>	US

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	5.00 in (12.7 cm)
<b>Package 1 Width</b>	7.50 in (19.05 cm)
<b>Package 1 Length</b>	15.62 in (39.687 cm)
<b>Package 1 Weight</b>	8.82 lb(US) (4 kg)

## Offer Sustainability

<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
<b>EU RoHS Directive</b>	Under investigation

## Recommended replacement(s)