750SV43F XFMR DRY 1PH .75KVA 120X240V-12/24V





Main

Man	
Product	Buck and Boost Transformer
Enclosure Code	6A
Enclosure Type	NEMA 3R
Insulation Temperature	356 °F (180 °C)
Primary Voltage	120 x 240 V
Power Rating	0.75 kVA
Secondary Voltage	12/24 V
Temperature Rise	115 °C

Ordering and shipping details

Category	16265 - BUCK & BOOST	
Discount Schedule	PE2	
GTIN	00785901019930	
Nbr. of units in pkg.	1	
Package weight(Lbs)	17.86 lb(US) (8.10 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Package 1 Height	7.00 in (17.780 cm)	
Package 1 width	8.40 in (21.336 cm)	
Package 1 Length	8.80 in (22.352 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months	