Product data sheet Characteristics

150SV43A XFMR DRY 1PH .15KVA 120X240V-12/24V



Main

Product	Buck and Boost Transformer
Enclosure Code	3A
Enclosure Type	NEMA 3R
Insulation Temperature	221 °F (105 °C)
Primary Voltage	120 x 240 V
Power Rating	0.15 kVA
Secondary Voltage	12/24 V
Temperature Rise	55 °C

Ordering and shipping details

Category	16265 - BUCK & BOOST	
Discount Schedule	PE2	
GTIN	00785901876090	
Nbr. of units in pkg.	1	
Package weight(Lbs)	7.8 lb(US) (3.54 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Package 1 Height	6.50 in (16.510 cm)	
Package 1 width	6.80 in (17.272 cm)	
Package 1 Length	8.00 in (20.320 cm)	

Offer Sustainability

PVC free	Yes
Environmental Disclosure	Product Environmental Profile
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Mercury free	Yes
Toxic heavy metal free	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
REACh free of SVHC	Yes
Sustainable offer status	Green Premium product

Contractual warranty

Contractadi Warranty		
Warranty	18 months	