

**Product Number:** 25384

**Order Abbreviation:** F84T12/CW/HO

**General Description:** 100W, 84" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI



**\* Full Case Required**

#### Product Information

|                              |                         |
|------------------------------|-------------------------|
| Abbrev. With Packaging Info. | F84T12CWHO 15/CS 1/SKU  |
| Actual Length (in)           | 81.909                  |
| Actual Length (mm)           | 2080.49                 |
| Average Rated Life (hr)      | 12000                   |
| Base                         | Recessed Double Contact |
| Bulb                         | T12                     |
| Color Rendering Index (CRI)  | 60                      |
| Color Temperature/CCT (K)    | 4200                    |
| Diameter (in)                | 1.593                   |
| Diameter (mm)                | 40.46                   |
| Industry Standards           | ANSI C78.81 - 2001      |
| Initial Lumens at 25C        | 7550                    |
| Mean Lumens at 25C           | 6115                    |
| Mean Lumens at 35C           | 6115                    |
| Nominal Length (in)          | 84.000                  |
| Nominal Length (mm)          | 2133.60                 |
| Nominal Wattage (W)          | 100.00                  |

#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.