# HDL36050

Breaking capacity code

Circuit breaker, PowerPact H, thermal magnetic, 50A, 3 pole, 600V, 14kA





# Main Product or component type Range of product PowerPact H Trip Unit Type Thermal-magnetic

Com			_ 1
L.Am	വമ	me	ntarv
OUITI	$\rho$ 1 $c$	1110	iitai y

Line Rated Current	50 A	
Number of Poles	3P	
Interrupt Rating	25 KA 240 V AC 18 KA 480 V AC 14 KA 600 V AC 20 kA 250 V DC	
[Ue] rated operational voltage	250 V DC 600 V AC	
Continuous current rating	80 %	
Mounting mode	Unit mount	
Electrical connection	Lugs load Lugs line	
Wire Gauge	AWG 14AWG 3/0 aluminium/copper	
Magnetic hold current	400 A	
Magnetic tripping current	850 A	
Maximum Height	6.4 in (162.56 mm)	
Maximum Width	4.12 in (104.65 mm)	
Maximum Depth	4.36 in (110.74 mm)	
Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) AWG 14AWG 3/0)	

#### Environment

Product certifications	IEC CE UL Listed CSA
Ambient air temperature for operation	104 °F (40 °C)

#### Ordering and shipping details

01110 - HD,JD UNIT MT BREAKER/SWITCH
DE2
00785901706700
1
4.05 lb(US) (1.84 kg)
Yes
MX

# Packing Units

•		
Unit Type of Package 1	PCE	
Package 1 Height	6.50 in (16.51 cm)	
Package 1 width	7.10 in (18.034 cm)	
Package 1 Length	9.10 in (23.114 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	80	
Package 2 Weight	329.84 lb(US) (149.613 kg)	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 width	36.00 in (91.44 cm)	
Package 2 Length	48.00 in (121.92 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	© REACh Declaration  Compliant © EU RoHS Declaration	
EU RoHS Directive		
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
PVC free	Yes	

## Contractual warranty

Warranty	18 months
----------	-----------

## **Approximate Dimensions**

