

# Product data sheet

## Characteristics

# 9998L44

Contacteur, Type L, multipole lighting, remplacement coil, 110/120 VAC 50/60 Hz, 8903L 2 to 6 poles, 8903LX 2 to 4 poles



### Main

|                                       |                      |
|---------------------------------------|----------------------|
| Product or component type             | Coil                 |
| Accessory / separate part destination | Class 8903 contactor |

### Complementary

|                                |                                  |
|--------------------------------|----------------------------------|
| [Ue] rated operational voltage | 120 V AC 60 Hz<br>110 V AC 50 Hz |
| Inrush power in VA             | 150 VA<br>140 VA                 |
| Average consumption            | 30 VA                            |
| Height                         | 2.38 in (60.5 mm)                |
| Width                          | 2.11 in (53.6 mm)                |
| Maximum Depth                  | 1.46 in (37.1 mm)                |

### Ordering and shipping details

|                       |                            |
|-----------------------|----------------------------|
| Category              | 21756 - 9998 DISCOUNT CP10 |
| Discount Schedule     | CP10                       |
| GTIN                  | 00785901081210             |
| Nbr. of units in pkg. | 1                          |
| Package weight(Lbs)   | 0.35 lb(US) (0.16 kg)      |
| Returnability         | Yes                        |
| Country of origin     | MX                         |

### Packing Units

|                  |                    |
|------------------|--------------------|
| Package 1 Height | 2.10 in (5.334 cm) |
| Package 1 width  | 2.80 in (7.112 cm) |
| Package 1 Length | 3.30 in (8.382 cm) |

### Offer Sustainability

|                       |  |
|-----------------------|--|
| EU RoHS Directive     | Under investigation  |
| China RoHS Regulation |  <a href="#">China RoHS Declaration</a> |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|