

Main

Wilder	
Marketing Trade Name	QO
Product Type	Load Center
Enclosure Type	Weatherproof enclosure
Cover Type	Surface cover

Complementary

1		
Tightening Torque	Main lugs 250 lb.in, AWG 4250 kcmil, aluminium/copper	
Load Center Type	Main lugs	
Rated Current	200 A	
Number of Spaces	30	
Max Short Circuit Current Rating	65 kA	
Maximum Number of Single Pole Circuits	30	
Maximum Number of Tandem Breakers	0	
Number of Phases	3 phase	
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC	
Wire Size	AWG 6300 kcmil aluminium/copper	
Ground Bar	Grounding bar included (not installed)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire 4-wire	
Busbar Material	Tin plated copper busbar	
Enclosure Material	Welded galvannealed steel	
Surface Finish	Baked enamel Gray	
Box Number	6R	
Height	29.84 in (758 mm)	
Width	14.76 in (375 mm)	

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	00017 - QO 3PH LOAD CENTER,OUTDOOR	
Discount Schedule	DE3	
GTIN	00785901295525	
Nbr. of units in pkg.	1	
Package weight(Lbs)	32.5 lb(US) (14.74 kg)	

Returnability	Yes
Country of origin	US
Packing Units	
Package 1 Height	31.70 in (80.518 cm)
Package 1 width	5.00 in (12.700 cm)
Package 1 Length	15.50 in (39.370 cm)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant [™] EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☐ China RoHS Declaration

Contractual warranty

Warranty	18 months