



## Main

|                              |   |
|------------------------------|---|
| Product                      | Single Throw Safety Switch                        |
| Current Rating               | 30 A  |
| Certifications               | UL listed file E2875                              |
| Enclosure Rating             | NEMA 1 steel                                      |
| Factory Installed Neutral    | None  |
| Disconnect Type              | Non-fusible disconnect                            |
| Short Circuit Current Rating | 200 kA maximum                                    |
| Mounting Type                | Surface   |
| Number of Poles              | 3   |
| Electrical Connection        | Lugs  |
| Duty Rating                  | Heavy duty  |
| Voltage Rating               | 600 V AC/DC                                       |
| Wire Size                    | AWG 12...AWG 6 aluminium<br>AWG 14...AWG 6 copper |

## Complementary

|                            |  |
|----------------------------|--|
| Short-circuit withstand    | 200 kA   |
| Maximum Horse Power Rating | 5 Hp 240 V AC 50...60 Hz 1 phase NEC 430.52<br>10 Hp 240 V AC 50...60 Hz 3 phase NEC 430.52<br>7.5 Hp 480 V AC 50...60 Hz 1 phase NEC 430.52<br>20 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52<br>10 Hp 600 V AC 50...60 Hz 1 phase NEC 430.52<br>30 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52<br>5 Hp 250 V DC NEC 430.52<br>15 hp 600 V DC |
| Maximum Height             | 14.6 in (370.84 mm)  |
| Maximum Depth              | 4.87 in (123.70 mm)  |
| Maximum Width              | 7.55 in (191.77 mm)  |
| Tightening torque          | 45 Lbf.In (5.08 N.m) 0.02 in <sup>2</sup> (13.3 mm <sup>2</sup> ) AWG 6)<br>40 Lbf.In (4.52 N.m) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) AWG 8)<br>35 lbf.in (3.95 N.m) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) AWG 14...AWG 10)   |

## Ordering and shipping details

|                       |                                 |
|-----------------------|---------------------------------|
| Category              | 00008 - H&HU SW,2&3P,N1,30-200A |
| Discount Schedule     | DE1                             |
| GTIN                  | 00785901505723                  |
| Nbr. of units in pkg. | 1                               |
| Package weight(Lbs)   | 7.6 lb(US) (3.45 kg)            |
| Returnability         | Yes                             |
| Country of origin     | US                              |

## Packing Units

|                              |                      |
|------------------------------|----------------------|
| Unit Type of Package 1       | PCE                  |
| Package 1 Height             | 5.20 in (13.208 cm)  |
| Package 1 width              | 7.70 in (19.558 cm)  |
| Package 1 Length             | 16.20 in (41.148 cm) |
| Unit Type of Package 2       | PAL                  |
| Number of Units in Package 2 | 120                  |

|                  |                            |
|------------------|----------------------------|
| Package 2 Weight | 948.00 lb(US) (430.005 kg) |
| Package 2 Height | 45.50 in (115.57 cm)       |
| Package 2 width  | 40.00 in (101.6 cm)        |
| Package 2 Length | 48.00 in (121.92 cm)       |

### Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free                   | Yes  |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Approximate Dimensions

