



Main

| | |
|---------------------------|------------------|
| Product or component type | Circuit breaker |
| Range of product | PowerPact H |
| Trip Unit Type | Thermal-magnetic |
| Breaking capacity code | D |

Complementary

| | |
|--------------------------------|---|
| Line Rated Current | 15 A |
| Number of Poles | 3P |
| Interrupt Rating | 25 KA 240 V AC 18 KA 480 V AC 14 KA 600 V AC 20 kA 250 V DC |
| [Ue] rated operational voltage | 250 V DC 600 V AC |
| Continuous current rating | 80 % |
| Mounting mode | Unit mount |
| Electrical connection | Lugs load Lugs line |
| Wire Gauge | AWG 14...AWG 3/0 aluminium/copper |
| Magnetic hold current | 350 A |
| Magnetic tripping current | 750 A |
| Maximum Height | 6.4 in (162.56 mm) |
| Maximum Width | 4.12 in (104.65 mm) |
| Maximum Depth | 4.36 in (110.74 mm) |
| Tightening torque | 44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0 |

Environment

| | |
|---------------------------------------|-------------------------------|
| Product certifications | IEC CE CSA UL Listed |
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| | |
|-----------------------|--------------------------------------|
| Category | 01110 - HD,JD UNIT MT BREAKER/SWITCH |
| Discount Schedule | DE2 |
| GTIN | 00785901577867 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 4.1 lb(US) (1.86 kg) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 5.80 in (14.732 cm) |
| Package 1 width | 7.40 in (18.796 cm) |
| Package 1 Length | 8.70 in (22.098 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Approximate Dimensions

