

# Product data sheet

## Characteristics

# 9998L55

Contacteur, Type L, multipole lighting, remplacement bobine, 277 VAC 60 Hz, 8903L 2 to 6 poles, 8903LX 2 to 4 poles



### Main

Product or component type	Coil
Accessory / separate part destination	Class 8903 contactor

### Complementary

[Ue] rated operational voltage	277 V AC 60 Hz
Inrush power in VA	150 VA
Average consumption	30 VA
Height	2.38 in (60.5 mm)
Width	2.11 in (53.6 mm)
Maximum Depth	1.46 in (37.1 mm)


### Ordering and shipping details

Category	21756 - 9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	00785901081241
Nbr. of units in pkg.	1
Package weight(Lbs)	0.34 lb(US) (0.15 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Package 1 Height	2.10 in (5.334 cm)
Package 1 width	2.80 in (7.112 cm)
Package 1 Length	3.40 in (8.636 cm)

### Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------