



Main

Range of product	Motor Logic
Thermal overload type	Solid state

Complementary

NEMA size	00
Phase	3 phase
Mounting support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	2.69 in (68.3 mm)
Width	3.26 in (82.8 mm)
Maximum Depth	3.90 in (99.1 mm)




Ordering and shipping details

Category	21662 - 9065 SOLID STATE OVERLOAD RELAYS
Discount Schedule	CP1
GTIN	00785901039686
Nbr. of units in pkg.	1
Package weight(Lbs)	1.12 lb(US) (0.51 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	5.60 in (14.224 cm)
Package 1 width	5.30 in (13.462 cm)
Package 1 Length	6.10 in (15.494 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------