

H322N

Safety switch, heavy duty, fusible, 60A, 3 poles, 15 hp, 240 VAC/250 VDC, neutral factory installed, NEMA1



Main

Product	Single Throw Safety Switch
Current Rating	60 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	250 V DC 240 V AC
Wire Size	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium

Complementary

Maximum Horse Power Rating	3 Hp 240 V AC 50...60 Hz 1 phase NEC 240.6 7.5 Hp 240 V AC 50...60 Hz 3 phase NEC 240.6 10 Hp 240 V AC 50...60 Hz 1 phase NEC 430.52 15 Hp 240 V AC 50...60 Hz 3 phase NEC 430.52 10 hp 250 V DC
Maximum Height	14.6 in (370.84 mm)
Maximum Depth	4.88 in (123.95 mm)
Maximum Width	6.5 in (165.10 mm)
Tightening torque	50 Lbf.In (5.65 N.m) AWG 3) 45 Lbf.In (5.08 N.m) AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) AWG 8) 50 lbf.in (5.65 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) AWG 14...AWG 10)

Ordering and shipping details

Category	00008 - H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	00785901480419
Nbr. of units in pkg.	1
Package weight(Lbs)	7.99 lb(US) (3.62 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.20 in (13.208 cm)
Package 1 width	7.70 in (19.558 cm)
Package 1 Length	16.10 in (40.894 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	105

Package 2 Weight	839.00 lb(US) (380.564 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------