



### Main

Product or component type	Dry Sealed Transformer
Primary Voltage	240 x 480 V
Full Capacity Taps	0
Secondary Voltage	120/240 V

### Complementary

Enclosure Code	4A
Phase	1 phase
Primary to Secondary Voltage	240 x 480 V 120/240 V
Power Rating	0.25 kVA
Temperature rise	80 °C
Maximum Height	5.5 in (139.70 mm)
Maximum Width	5.23 in (132.84 mm)
Maximum Depth	4.06 in (103.12 mm)
Enclosure mounting	Wall mounted
Enclosure material	Painted sheet steel

### Environment

Enclosure Type	NEMA 3R
Insulation temperature	266 °F (130 °C)
Product certifications	CULus CSA UL Listed

### Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901019824
Nbr. of units in pkg.	1
Package weight(Lbs)	9.7 lb(US) (4.40 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Package 1 Height	6.70 in (17.018 cm)
Package 1 width	6.80 in (17.272 cm)
Package 1 Length	7.80 in (19.812 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------