



### Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard

### Complementary

Line Rated Current	80 A
Number of Poles	3P
Interrupt Rating	10 KA 120/240 V AC 10 KA 240 V AC 10 KA 120 V AC 5 kA 60 V DC
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC 240 V AC 120 V AC 60 V DC
Mounting mode	Unit mount
AWG gauge	AWG 12...AWG 2/0 aluminium/copper
Maximum Height	4.45 in (113.03 mm)
Maximum Depth	2.95 in (74.93 mm)
Maximum Width	2.25 in (57.15 mm)
Tightening torque	45 lbf.in (5.08 N.m) AWG 12...AWG 2/0)

### Environment

Product certifications	CSA UL Listed IEC
------------------------	-------------------------

### Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901060314
Nbr. of units in pkg.	1
Package weight(Lbs)	1.43 lb(US) (0.65 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	2.50 in (6.350 cm)
Package 1 width	3.50 in (8.890 cm)
Package 1 Length	4.80 in (12.192 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------