QO2100BNF

Load center enclosure, QO, 1 phase, 2 spaces, used with 100A breaker, NEMA1, flush cover, UL





Main

- Trickini	
Marketing Trade Name	QO
Product Type	Enclosure
Enclosure Type	Enclosure
Cover Type	Flush cover

Complementary

Tightening Torque	35 lb.in, AWG 14AWG 10, copper	
. ig.i.c.ig . c.iquo	35 lb.in, AWG 12AWG10, aluminium	
	40 lb.in, AWG 8AWG 4, aluminium/copper	
	50 lb.in, AWG 3AWG 2, aluminium/copper	
	Main lugs 50 lb.in, AWG 3AWG 1, aluminium/copper	
Rated Current	100 A	
Number of Spaces	2	
Max Short Circuit Current Rating	22 kA	
Maximum Number of Single Pole Circuits	2	
Maximum Number of Tandem Breakers	0	
Number of Phases	1 phase	
Wire Size	AWG 14AWG 1 copper	
	AWG 12AWG 1 aluminium	
Ground Bar	Grounding bar (ordered separately)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Busbar Material	Tin plated copper busbar	
Enclosure Material	Welded sheet steel	
Surface Finish	Baked enamel Gray	
Box Number	13	
Height	13.11 in (333 mm)	
Width	5.87 in (149 mm)	

Environment

Enclosure Rating	NEMA 1 indoor
Product Certifications	UL Listed

Ordering and shipping details

00005 - QO,Q2L 2P ENCL & BREAKERS
DE2A
00785901051725
1
5.74 lb(US) (2.60 kg)

Returnability	Yes
Country of origin	MX
Packing Units	
Package 1 Height	4.40 in (11.176 cm)
Package 1 width	7.60 in (19.304 cm)
Package 1 Length	15.00 in (38.100 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

18 months

Contractual warranty

Warranty