

# Product data sheet

## Characteristics

# 8911DPSG52V09

Starter, Definite Purpose, nonreversing, 50A, 2 pole, 1 phase, 208 to 240 VAC coil, melting alloy overload, NEMA 1



### Main

Product	Definite Purpose Starter
Ampere Rating	50 A
Horsepower Rating	3 Hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	220 V AC 50 Hz 208...240 V AC 60 Hz
Phase	1 phase

### Complementary

Enclosure Material	Painted sheet steel
Enclosure Rating	NEMA 1
Locked Rotor Amperes	300 A 230 V AC 250 A 460 V AC 200 A 575 V AC
Number of Poles	2P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	1

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901024835
Nbr. of units in pkg.	1
Package weight(Lbs)	9.34 lb(US) (4.24 kg)
Returnability	Yes
Country of origin	CN

### Packing Units

Package 1 Height	7.70 in (19.558 cm)
Package 1 width	8.80 in (22.352 cm)
Package 1 Length	13.50 in (34.290 cm)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

---

Warranty

18 months

---