QO112L200PGRB

Load center, QO, 1 phase, 12 spaces, 24 circuits, 200A convertible main lugs, PoN, NEMA3R, gnd bar, UL



Main

Marketing Trade Name	QO
Product Type	Load Center
Enclosure Type	Weatherproof enclosure
Provided Equipment	Grounding bar

Complementary

Load Center Type	Main lugs	
Rated Current	200 A	
Number of Spaces	12	
Max Short Circuit Current Rating	65 kA	
Maximum Number of Single Pole Circuits	24	
Maximum Number of Tandem Breakers	12	
Number of Phases	1 phase	
Ground Bar	Grounding bar included (not installed)	
Box Number	5R	
Height	26.04 in (661.42 mm)	
Width	14.75 in (374.65 mm)	
Depth	4.52 in (114.81 mm)	

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering and shipping details

Category	10002 - QO PON 1PH LC,12-60 CKT, N3R	
Discount Schedule	DE3A	
GTIN	00785901594703	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1 lb(US) (0.45 kg)	
Returnability	Yes	
Country of origin	US	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration