



Product Number: 67502

Order Abbreviation: LU50/MED

General Description: 50W LUMALUX high pressure sodium HID lamp, E26 based, E17 bulb, universal burn, clear, 1900K

Product Information

| | |
|---------------------------------------|---------------------|
| Abbrev. With Packaging Info. | LU50MED 20/CS 1/SKU |
| ANSI Code | S68 |
| ANSI Code 2 | S68 |
| Approx. Lumens (initial - horizontal) | 4000 |
| Approx. Lumens (initial - vertical) | 4000 |
| Approx. Lumens (mean - horizontal) | 3600 |
| Approx. Lumens (mean - vertical) | 3600 |
| Arc Length (in) | 0.89 |
| Arc Length (mm) | 22.5 |
| Average Rated Life - Horizontal (hr) | 24000 |
| Average Rated Life - (hr) | 24000 |
| Avg Rated Life (hrs) | 24000+ |
| Base | E26 Medium |
| Bulb | E17 |
| Color Rendering Index (CRI) | 21 |
| Color Temperature/CCT (K) | 1900 |
| Diameter (in) | 2.126 |
| Diameter (mm) | 54.00 |
| Family Brand Name | Lumalux® |
| Fixture Requirement | O |
| Hot Restrike Time (min) | 1 MIN |
| Lamp Finish | Clear |
| Light Center Length - LCL (in) | 3.42 |
| Light Center Length - LCL (mm) | 87 |
| Maximum Base Temperature - Fahrenheit | 410 |
| Maximum Base Temperature - Celsius | 210 |
| Maximum Bulb Temperature - Fahrenheit | 725 |
| Maximum Bulb Temperature - Celsius | 385 |
| Maximum Overall Length - MOL (in) | 5.43 |
| Maximum Overall Length - MOL (mm) | 138 |
| Nominal Voltage (V) | 52.00 |
| Nominal Wattage (W) | 50.00 |
| Operating Position | Universal |
| Warm-up Time (min) | 3-4 MINUTES |

Footnotes

- Use with 4000V pulse rated sockets only.
- Mean lumens measured at 50% of average rated life