9080GR6

Terminal Block, box lug connector, 60 A, 600 VAC/DC, natural colored block



Main

Range of product	9080G
Product Type	Terminal block
Localisation on Device	Standard
Color	Natural
Quantity	Set of 50

Complementary

Voltage Rating	600 V AC/DC
Current Rating	60 A UL
	60 A CSA
Wire Size	AWG 22AWG 8 copper
Mounting Type	35 mm DIN rail
	9080GH track
Certifications	UL recognized E60616 CCN XCFR2
	CE
	CSA file 62144 class 6228 01
Protection Type	Fingersafe DIN 57470
Electrical Connection	Copper box lugs
Material	Nylon block
Ambient air temperature for operation	-40257 °F (-40125 °C)
Electrical Connrection Tightening Torque	Lug copper 1820 lbf.in (2.032.26 N.m) : AWG 22AWG 8 copper)
Height	1.82 in (46.23 mm)
Width	1.72 in (43.69 mm)
Maximum Depth	0.35 in (8.89 mm)
Density	34 per foot
Compatible End Barrier	GM6B
Net Weight	0.02 lb(US) (0.01 kg)

Ordering and shipping details

0 11 0	
Category	21702 - 9080 G (NOT GCB)
Discount Schedule	CP5
GTIN	00785901000716
Nbr. of units in pkg.	50
Package weight(Lbs)	0.03 lb(US) (0.01 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	5.08 in (12.903 cm)
Package 1 width	2.00 in (5.080 cm)
Package 1 Length	12.90 in (32.774 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	[™] China RoHS Declaration
PVC free	Yes

Contractual warranty

14/	40 months
vvarranty	18 months