HOM24L70S

Load center, Homeline, 1 phase, 2 spaces, 4 circuits, 70A fixed main lugs, NEMA1, surface cover





Main	
Product or component type	Load Center
Marketing Trade Name	Homeline
Load center type	Main lugs
Line Rated Current	70 A
Number of spaces	2
Number of circuits	4
Enclosure Rating	NEMA 1 indoor
Cover type	Surface cover

Lugs

Complementary

10 kA	
2	
1 phase	
120/240 V AC	
AWG 12AWG 3 aluminium AWG 14AWG 4 copper	
3-wire	
Gray baked enamel	
Tin plated aluminium busbar	
Welded sheet steel	
Baked enamel Gray	
2	
9.29 in (236 mm)	
4.80 in (122 mm)	
3.19 in (81 mm)	
	2 1 phase 120/240 V AC AWG 12AWG 3 aluminium AWG 14AWG 4 copper 3-wire Gray baked enamel Tin plated aluminium busbar Welded sheet steel Baked enamel Gray 2 9.29 in (236 mm) 4.80 in (122 mm)

Electrical connection

Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)	
Product certifications	UL E-6294	

Ordering and shipping details

Category	00149 - HOM 2-8 CKT,MLO,NEMA1&3R
Discount Schedule	DE3C
GTIN	00785901061168
Nbr. of units in pkg.	1
Package weight(Lbs)	3.86 lb(US) (1.75 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	4.00 in (10.160 cm)	
Package 1 width	6.60 in (16.764 cm)	
Package 1 Length	11.10 in (28.194 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	Lifetime