



Main

Product Range	Type S
Component type	Selector switch
Used with	Contactors starter

Complementary

NEMA size	00 1 0 2 3
Marking	HAND-OFF-AUTO
Mounting mode	Panel-mounted
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 0.6 A 600 V AC inductive control circuit UL 508 5 A 600 V AC resistive control circuit UL 508
Height	1.88 in (47.75 mm)
Width	3.81 in (96.77 mm)
Maximum Depth	5.63 in (143.00 mm)
Net Weight	0.51 lb(US) (0.23 kg)

Environment

NEMA degree of protection	NEMA 1
Product certifications	UL Listed UL Recognized CSA

Ordering and shipping details

Category	21761 - 9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901783008
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5 lb(US) (0.23 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	2.00 in (5.080 cm)
Package 1 width	3.80 in (9.652 cm)
Package 1 Length	5.70 in (14.478 cm)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------