NF442L4C

Panelboard interior, NF, main lugs, 400A, Cu bus, 42 pole spaces, 3 phase, 4 wire, 600Y/347 VAC max





Main

Panelboard Type	Main lugs	
Branch Circuit Breaker Type	EDB/EDG/EDJ	
Busbar Material	Copper	

Complementary

Number of spaces	42
Enclosure Nominal Height	68 ln (1727.20 mm) 56 in (1422.40 mm)
Enclosure Nominal Width	20 in (508.00 mm)
Enclosure Nominal Depth	5.75 In (146.05 mm) NEMA 1 6.5 in (165.10 mm) NEMA 3R/5/12
Line Rated Current	400 A
[lu] rated interrupted current	65 kA
Wiring configuration	4-wire
Number of Phases	3 phase
Voltage Rating	600Y/347 V AC
Connections - terminals	Lug line AWG 1/0750 kcmil aluminium Lug neutral AWG 1/0750 kcmil aluminium
Net Weight	59.00 lb(US) (26.76 kg)
Tightening torque	274.99300.04 Lbf.In (31.0733.90 N.m) 0.080.59 in² (53.48380 mm²) AWG 1/0750 kcmil) 274.99300.04 Lbf.In (31.0733.90 N.m) 0.080.27 in² (53.48177.3 mm²) AWG 1/0350 kcmil) 549.98 Lbf.In (62.14 N.m) 0.080.59 in² (53.48380 mm²) AWG 1/0750 kcmil) 549.98 Lbf.In (62.14 N.m) 0.080.24 in² (53.48152 mm²) AWG 1/0300 kcmil) 375.01 Lbf.In (42.37 N.m) 0.080.24 in² (53.48380 mm²) AWG 1/0750 kcmil) 375.01 lbf.in (42.37 N.m) 0.080.24 in² (53.48152 mm²) AWG 1/0300 kcmil)
Width	10.44 in (265.18 mm)
Height	52 in (1320.80 mm)

Environment

Standards	CSA C22.2
	UL 67

Ordering and shipping details

Category	08350 - NF MLO INTERIOR RTA	
Discount Schedule	PE1A	
GTIN	00785901871613	
Nbr. of units in pkg.	1	
Package weight(Lbs)	31.18 lb(US) (14.14 kg)	

Returnability	Yes
Country of origin	US
Packing Units	
Package 1 Height	0.50 ft (0.152 m)
Package 1 width	1.15 ft (0.351 m)
Package 1 Length	4.42 ft (1.346 m)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

18 months

Contractual warranty

Warranty