JDA36225

Circuit breaker, PowerPact J, I-Line, thermal magnetic, 225A, 3 pole, 14 kA, 600 VAC, phase ABC





Main	
Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking canacity code	D

Complementary

Palas description	2D	-
Poles description	3P	
[Ue] rated operational voltage	25 KA 240 V AC	
	18 KA 480 V AC	
	14 KA 600 V AC	
	20 kA 250 V DC	
[Ue] rated operational voltage	600 V AC	
	250 V DC	
Mounting mode	I-Line	
Electrical connection	I-Line connection line	
	Lugs load	
AWG gauge	AWG 3/0350 kcmil aluminium/copper	
Phase connection	ABC	

Environment

Product certifications	CSA	
	UL Listed	
	CE	
	IEC	
	IEC CCC	

Ordering and shipping details

0 11 0	
Category	01112 - HD, JD I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901834168
Nbr. of units in pkg.	1
Package weight(Lbs)	6.6 lb(US) (2.99 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	6.00 in (15.24 cm)	
Package 1 width	8.50 in (21.59 cm)	
Package 1 Length	14.80 in (37.592 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Contractual warranty

Warranty	18 months
----------	-----------