# Product data sheet Characteristics

# QO403L60NS LOAD Center QO MLO 240V 60A 3PH 3SP N1



### Main

Marketing Trade Name	QO
Product Type	Load Center
Cover Type	Surface cover

### Complementary

Complementary		
Tightening Torque	Main lugs 35 lb.in, AWG 14AWG 10, aluminium/copper Main lugs 50 lb.in, AWG 3AWG 1, aluminium/copper Main lugs 40 lb.in, AWG 8AWG 4, aluminium/copper Main lugs 35 lb.in, AWG 12AWG10, aluminium/copper	
Load Center Type	Main lugs	_
Rated Current	60 A	
Number of Spaces	3	
Max Short Circuit Current Rating	65 kA	
Maximum Number of Single Pole Circuits	3	
Maximum Number of Tandem Breakers	0	
Number of Phases	3 phase	
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC	
Wire Size	AWG 10AWG 6 copper	_
Ground Bar	Neutral (factory installed)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire 4-wire	
Busbar Material	Tin plated aluminium busbar	
Enclosure Material	Welded sheet steel	
Surface Finish	Baked enamel Gray	
Box Number	13	
Height	13.11 in (333 mm)	
Width	5.87 in (149 mm)	

#### Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

## Ordering and shipping details

Category	00011 - QO 3PH LOAD CENTER,INDOOR
Discount Schedule	DE3
GTIN	00785901051701
Nbr. of units in pkg.	1
Package weight(Lbs)	5.74 lb(US) (2.60 kg)
Returnability	Yes
Country of origin	MX

# Packing Units

Package 1 Height	3.80 in (9.652 cm)
Package 1 width	7.60 in (19.304 cm)
Package 1 Length	15.20 in (38.608 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration

### Contractual warranty

Warranty 1	8 months
------------	----------