



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

BITO600  
 7818102252644  
 600-4, OFFSET, UNITAP  
 Active

**Web Use**  
 BURNDY Product Line

Width (in)  
 Hex Size (Key)  
 Length (in)  
 Height (in)

**Dimensional**  
 3.00  
 3/8  
 2.72  
 2.75

Min Voltage Rating

**Electrical**  
 600

Number of Ports  
 Number of Screws

**General**  
 2  
 2

Product Description

Aluminum Multiple Tap  
 Connector, Clear Insulated, 2 Port,  
 2 Sided Entry, 4 AWG-600 kcmil,  
 Al/Cu Rated

Aluminum Size (Range)  
 Copper Solid Size (Range)  
 Copper Stranded (Range)

**Conductor(s)**  
 4 AWG-600 kcmil  
 N/A  
 4 AWG-600 kcmil

Type of Hardware  
 Type of Plating  
 Insulation Type  
 Plated (Yes or No)  
 Product Material

**Physical**  
 Aluminum  
 Unplated  
 Plastisol  
 N  
 Aluminum

Rated for Direct Burial  
 UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS  
 Industry Standards

**Approvals / Certifications**

N  
 Y  
 Y  
 Compliant  
 N  
 N  
 UL468A-468B

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175