

D325NR

Safety switch, general duty, fusible, 400A, 3 poles, 125 hp, 240 VAC, NEMA 3R, neutral factory installed



Main

Product	Single Throw Safety Switch
Current Rating	400 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Short Circuit Current Rating	100 kA maximum depending on fuse H, K, J or R
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 10...AWG 6 aluminium/copper

Complementary

Maximum Horse Power Rating	50 Hp 240 V AC 60 Hz 3 phase NEC 240.6 125 hp 240 V AC 60 Hz 3 phase NEC 430.52
Maximum Width	22.25 in (565.15 mm)
Maximum Height	30.63 in (778.00 mm)
Maximum Depth	10.13 in (257.30 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 1/0...250 kcmil

Ordering and shipping details

Category	00107 - D & DU SW,NEMA3R, 400-600A
Discount Schedule	DE1A
GTIN	00785901461579
Nbr. of units in pkg.	1
Package weight(Lbs)	69.98 lb(US) (31.74 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.00 in (27.94 cm)
Package 1 width	23.00 in (58.42 cm)
Package 1 Length	32.00 in (81.28 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

