

## TYPE T4A4

### Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Must be mounted with a minimum of 4 bolts
- Rated to 90° C

### Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Application versatility




Fig. 1



Fig. 2



Fig. 3



Fig. 4

Catalog Number	Figure Number	Wire Range	Bolt Size	Dimensions									Hex Size
				C	E	F	G	H	J	K	R	T	
T4A4-250N*	1	250kcmil-6	1/2	9/16	3	4	5/8	3-49/64	1-3/4	5/16	1-3/16	1-17/32	5/16
T4A4-350N*	1	350kcmil-6	1/2	9/16	3	4-5/16	5/8	4-1/64	1-3/4	5/16	1-3/8	1-17/32	5/16
T4A4-600N*	3	600kcmil-2	1/2	9/16	3-1/4	5-1/2	5/8	5	1-3/4	3/8	1-1/2	1-7/8	1/2
T4A4-800N*	2	800kcmil-300kcmil	1/2	9/16	3-5/8	5-31/32	5/8	6	1-3/4	1/2	1-13/16	2-13/64	1/2
T4A4-1000N*	4	1000kcmil-350kcmil	1/2	9/16	3-5/8	5-31/32	5/8	6-1/2	1-3/4	1/2	1-13/16	2-13/64	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

DE-OX Inhibitor is recommended for all aluminum terminations.

Tested to UL 486A/B, UL File E6207

\* Mounting hole spacing from side to side, hole to hole is .875