



Product Number: 64037

Order Abbreviation: M400/C/U/ED37

General Description: 400W METALARC quartz metal halide lamp, E39 base, ED37 bulb, enclosed fixture rated, universal burn, coated, 3700K

Product Information

Abbrev. With Packaging Info.	M400CUED37 6/CS 1/SKU
ANSI Code 2	M59/S
Approx. Lumens (initial - horizontal)	32000
Approx. Lumens (initial - vertical)	36
Approx. Lumens (mean - horizontal)	3
Approx. Lumens (mean - vertical)	23
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	ED37
Color Rendering Index (CRI)	70
Color Temperature/CCT (K)	3700
Diameter (in)	4.606
Diameter (mm)	117
Family Brand Name	Metalarc®
Fixture Requirement	S
Hot Restrike Time (min)	7 - 12
Lamp Finish	Coated
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Voltage (V)	135.00
Nominal Wattage (W)	400.00
Operating Position	Universal
Warm-up Time (min)	2 - 4

Footnotes

- 20,000 average rated life based on 10 hrs/start. 30,000 average rated life based on 120 hrs/start.
- S = When operated within 15 degrees of vertical, this lamp may be operated in an open luminaire provided the installation is not near people or flammable or combustible material, otherwise it must be operated in a suitably enclosed luminaire. See lamp warning.