2510MBG2

Manual Starter, integral horsepower, NEMA M0, 600 VAC, 3 pole, 5 HP at 380/575 VAC, three phase, no indicator, NEMA 1



Main

Product	Manual Starter
Туре	M
NEMA Size	M-0

Complementary

Complementary		
Control Unit	Push-button	
Pilot Light	No indicator	
Horsepower Rating	3 Hp 200230 V AC, 3 phase 5 hp 380575 V AC, 3 phase	
Voltage Rating	600 V AC	
Number of Poles	3P	
Starter Type	Non reversing	
Electrical Connection	Pressure wire clamp	
Overload Relay Type	Melting alloy	
Number of Thermal Units Required	3	
Wire Gauge	AWG 14AWG 8 copper	
Auxiliary Contacts	Without	
Height	8.63 in (219.20 mm)	
Width	5 in (127.00 mm)	
Maximum Depth	4.13 in (104.90 mm)	
Net Weight	4.14 lb(US) (1.88 kg)	

Environment

Certifications	CSA LR60905 class 3211 05 UL listed file E42243 CCN NLRV
NEMA Enclosure Rating	NEMA 1 painted sheet steel

Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T	
Discount Schedule	CP1	
GTIN	00785901792536	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.15 lb(US) (1.88 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.60 in (11.684 cm)
Package 1 width	5.70 in (14.478 cm)
Package 1 Length	9.10 in (23.114 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	126
Package 2 Weight	535.00 lb(US) (242.672 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months

Approximate Dimensions

