

Main

| | |
|------------------------|------------------------|
| Product | Transformer Disconnect |
| Certifications | UL Listed CSA |
| Enclosure Type | NEMA 1 standard |
| Insulation Temperature | 356 °F (180 °C) |
| Phase | 1 phase |
| Primary Voltage | 240 x 480 V |
| Power Rating | 1000 VA |
| Secondary Voltage | 120 V |
| Temperature Rise | 115 °C |
| Electrical Connection | Screw clamp terminals |
| Type | SK |

Ordering and shipping details

| | |
|-----------------------|----------------------|
| Category | 21694 - 9070 SK |
| Discount Schedule | CP8 |
| GTIN | 00785901099420 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 37 lb(US) (16.78 kg) |
| Returnability | No |
| Country of origin | US |

Packing Units

| | |
|------------------|----------------------|
| Package 1 Height | 11.80 in (29.972 cm) |
| Package 1 width | 11.50 in (29.210 cm) |
| Package 1 Length | 15.40 in (39.116 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|