



## Main

Product	Switch Weatherproof enclosure
Range	QO
Current Rating	60 A
Voltage Rating	240 V AC
Color	Gray

## Complementary

Interrupt Rating	22 kA 240 V AC
Maximum Height	6.50 in (165 mm)
Maximum Depth	3.90 in (99 mm)
Maximum Width	4.65 in (118 mm)
Number of Phases	1 phase
Indoor/Outdoor Use	Enclosed outdoor
For Use With	Air conditioner

## Environment

Certifications	UL Listed
Ambient Rating	104 °F (40 °C)
NEMA Enclosure Rating	NEMA 3R

## Ordering and shipping details

Category	00044 - A/C DISC & PULL-OUTS
Discount Schedule	DE2A
GTIN	00785901535966
Nbr. of units in pkg.	1
Package weight(Lbs)	3 lb(US) (1.36 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.50 in (8.89 cm)
Package 1 width	4.20 in (10.668 cm)
Package 1 Length	6.50 in (16.51 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	30.35 lb(US) (13.767 kg)
Package 2 Height	7.10 in (18.034 cm)
Package 2 width	9.80 in (24.892 cm)
Package 2 Length	19.80 in (50.292 cm)
Unit Type of Package 3	PAL

Number of Units in Package 3	400
Package 3 Weight	1270.00 lb(US) (576.062 kg)
Package 3 Height	42.00 in (106.68 cm)
Package 3 width	40.00 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

