



BURNDY Catalog Number
UPC Number
Description
Status

BIBD6006
7818102241822
600-4 TWO SIDED UNITAP
Active

Web Use
BURNDY Product Line

Width (in)
Hex Size (Key)
Length (in)
Height (in)

Dimensional
3.00
3/8
7.37
2.75

Min Voltage Rating

Electrical
600

Number of Ports
Number of Screws

General
6
6

Product Description

Aluminum Multiple Tap
Connector, Clear Insulated, 6 Port,
2 Sided Entry, 4 AWG-600 kcmil,
Al/Cu Rated

Aluminum Size (Range)
Copper Solid Size (Range)
Copper Stranded (Range)

Conductor(s)
4 AWG-600 kcmil
N/A
4 AWG-600 kcmil

Type of Hardware
Type of Plating
Insulation Type
Plated (Yes or No)
Product Material

Physical
Aluminum
Unplated
Plastisol
N
Aluminum

Rated for Direct Burial
UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS
Industry Standards

Approvals / Certifications

N
Y
Y
Compliant
N
N
UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175