# 9998DA2V09

Contactor, Definite Purpose, replacement coil, 220/240 VAC 50/60 Hz, for 8910DPA 50A and 60A contactors, 2 and 3 poles



Main		
Product or component type	Coil	
Accessory / separate part destination	8910DPA contactor	

Complementary

[Ue] rated operational voltage	208/240 V AC 60 Hz	
	220 V AC 50 Hz	
Inrush power in VA	109 VA	
Average consumption	10 VA	
Height	3.27 in (83.06 mm)	
Width	2.56 in (65.02 mm)	
Maximum Depth	3.67 in (93.22 mm)	

Ordering and shipping details

Category	21752 - 9998 DISCOUNT CP1B
Discount Schedule	CP1B
GTIN	00785901081456
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	CN

## **Packing Units**

Package 1 Height	1.70 in (4.318 cm)
Package 1 width	2.60 in (6.604 cm)
Package 1 Length	3.50 in (8.890 cm)

#### Offer Sustainability

☑ REACh Declaration	
Compliant	
Yes	
€Yes	
<sup>™</sup> China RoHS Declaration	
	Compliant E EU RoHS Declaration  Yes  Yes

## Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## **Approximate Dimensions**

