## HOM1224L125PC

Load center, Homeline, 1 phase, 12 spaces, 24 circuits, 125A convertible main lugs, PoN, NEMA1, combo cover





#### Main Product or component Load Center type Marketing Trade Name Homeline Load center type Main lugs 125 A Line Rated Current Number of spaces 12 Number of circuits 24 **Enclosure Rating** NEMA 1 indoor

Combination flush/surface cover

Complementary

10 kA	
6	
1 phase	
120/240 V AC	
AWG 6AWG 2/0 aluminium AWG 6AWG 1 copper	
3-wire	
Tin plated aluminium busbar	
Baked enamel Gray	
17.91 in (455 mm)	
14.25 in (362 mm)	
3.74 in (95 mm)	
	1 phase 120/240 V AC AWG 6AWG 2/0 aluminium AWG 6AWG 1 copper 3-wire Tin plated aluminium busbar Baked enamel Gray 17.91 in (455 mm) 14.25 in (362 mm)

Cover type

Electrical connection

#### Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL E-6294

#### Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1	
Discount Schedule	DE3C	
GTIN	00785901876120	
Nbr. of units in pkg.	1	
Package weight(Lbs)	17.8 lb(US) (8.07 kg)	
Returnability	Yes	
Country of origin	US	

### Packing Units


3		
Unit Type of Package 1	PCE	
Package 1 Height	5.70 in (14.478 cm)	
Package 1 width	16.20 in (41.148 cm)	
Package 1 Length	20.60 in (52.324 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	42	
Package 2 Weight	747.00 lb(US) (338.833 kg)	
Package 2 Height	43.00 in (109.22 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

### Offer Sustainability

Green Premium product	
Yes	
Compliant E EU RoHS Declaration	
Yes	
Yes	
₫Yes	
☑ China RoHS Declaration	
Product Environmental Profile	
	Yes  Compliant E EU RoHS Declaration  Yes  Yes  Yes  China RoHS Declaration

# HOM1224L125PC

#### **Approximate Dimensions**



# HOM1224L125PC

#### Connections and Wiring Diagrams

