

TYPE GTC

Features

- Snap closure
- Color coded
- UL Listed and CSA Certified for 600 volts, 90° C except for GTPC-750-750 and GTTC-750-750

Benefits

- Installs quickly and saves labor time by eliminating taping
- Provides ease of identification in the field
- Ensures reliability



Fig. 1



Fig. 2



Fig. 3

B

Catalog Number	Figure Number	Color	Dimensions			Used with Connector
			L	W	H	
GTC-2	1	Black	2-1/4	1-13/16	1-1/4	GTA-2-2: GTT-2-2
GTC-0	1	Black	2-1/2	2-3/32	1-3/8	GTA-0-0: GTT-0-0
GTC-250-350	1	Black	3-61/64	3-1/32	2	GTA-250-0: GTA-250-250 GTA-350-350 GTT-250-0: GTT-250-250 GTT-350-350
GTC-500	1	Black	4-1/8	3-1/16	2-31/32	GTA-500-500 GTT-500-500
GTC-750-500	1	Black	4-7/8	3-1/8	2-23/32	GTA-750-500 GTT-750-500
GTPC-750-750*	2	Black	4-7/8	4	2-7/8	GTA-750-750
GTTC-750-750*	3	Black	5-3/4	4-1/4	3-1/16	GTT-750-750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Not UL Listed or CSA Certified

Tested to UL 486A/B, UL File E6207

TYPE GTC

Features

- Snap closure
- Color coded
- UL Listed and CSA Certified for 600 volts, 90° C except for GTPC-750-750 and GTTC-750-750

Benefits

- Installs quickly and saves labor time by eliminating taping
- Provides ease of identification in the field
- Ensures reliability



Fig. 1



Fig. 2



Fig. 3

Catalog Number	Figure Number	Color	Dimensions			Used with Connector
			L	W	H	
GTC-2	1	Black	2-1/4	1-13/16	1-1/4	GTA-2-2: GTT-2-2
GTC-0	1	Black	2-1/2	2-3/32	1-3/8	GTA-0-0: GTT-0-0
GTC-250-350	1	Black	3-61/64	3-1/32	2	GTA-250-0: GTA-250-250 GTA-350-350 GTT-250-0: GTT-250-250 GTT-350-350
GTC-500	1	Black	4-1/8	3-1/16	2-31/32	GTA-500-500 GTT-500-500
GTC-750-500	1	Black	4-7/8	3-1/8	2-23/32	GTA-750-500 GTT-750-500
GTPC-750-750*	2	Black	4-7/8	4	2-7/8	GTA-750-750
GTTC-750-750*	3	Black	5-3/4	4-1/4	3-1/16	GTT-750-750

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

* Not UL Listed or CSA Certified

Tested to UL 486A/B, UL File E6207