

D321N

Safety switch, general duty, fusible, 30A, 3 poles, 7.5 hp, 240 VAC, NEMA 1, neutral factory installed



Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 14...AWG 6 copper AWG 12...AWG 6 aluminium

Complementary

Maximum Horse Power Rating	1.5 Hp 240 V AC 60 Hz 1 phase NEC 240.6 3 Hp 240 V AC 60 Hz 3 phase NEC 240.6 3 Hp 240 V AC 60 Hz 1 phase NEC 430.52 7.5 hp 240 V AC 60 Hz 3 phase NEC 430.52
Maximum Width	7.25 in (184.15 mm)
Maximum Height	9.25 in (234.95 mm)
Maximum Depth	3.63 in (92.20 mm)
Tightening torque	30 lbf.in (3.39 N.m) 0.00...0.02 in ² (2.08...13.3 mm ²) AWG 14...AWG 6)

Ordering and shipping details

Category	00006 - D & DU SW, NEMA1, 30-200A
Discount Schedule	DE1A
GTIN	00785901461036
Nbr. of units in pkg.	1
Package weight(Lbs)	4.45 lb(US) (2.02 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.20 in (13.208 cm)
Package 1 width	6.80 in (17.272 cm)
Package 1 Length	9.20 in (23.368 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	23.25 lb(US) (10.546 kg)
Package 2 Height	9.90 in (25.146 cm)
Package 2 width	8.90 in (22.606 cm)
Package 2 Length	19.30 in (49.022 cm)

Unit Type of Package 3	PAL
Number of Units in Package 3	150
Package 3 Weight	699.00 lb(US) (317.061 kg)
Package 3 Height	40.00 in (101.6 cm)
Package 3 width	40.00 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------