9001KA1G PUSH BUTTON CONTACT 600VAC 10A 30MM T-K





Main

IVICIII			
Range of pro	oduct	Harmony 9001K	
Product or c type	omponent	Contact block	
Device short	name	K	

Complementary

Contact operation	Series G style
Short-circuit protection	10 A without fingersafe

Environment

Product certifications	UL listed file E42259 CCN NKCR	
	CSA LR 25490 class 3211 03	
	CE	

Ordering and shipping details

21434 - 9001 KA CONTACT BLOCKS	
CS1	
00785901028789	
1	
0.06 lb(US) (0.03 kg)	
Yes	
MX	
	CS1 00785901028789 1 0.06 lb(US) (0.03 kg) Yes

Packing Units

Package 1 Height	2.54 in (6.452 cm)	
Package 1 width	1.00 in (2.540 cm)	
Package 1 Length	6.45 in (16.387 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	

China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
Contractual warranty		
Warranty	18 months	