Product data sheet Characteristics

LA36400 3P 400A 600V, LA FA/LA MOLDED CASE CIRCUIT BREAKER





Main Product or component Circuit breaker type

Range of product	I-Line	
Trip Unit Type	Thermal-magnetic	
Rating Code	Α	

Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	42 KA 120 V AC
	42 KA 240 V AC
	30 KA 480Y/277 V AC
	30 KA 480 V AC
	22 KA 600 V AC
	10 KA 125 V DC
	10 kA 250 V DC
[Ue] rated operational voltage	600 V AC
[or] rates of eventual ratings	250 V DC
Mounting mode	I-Line
Electrical connection	Lugs load
	I-Line connection line
Wire Gauge	AWG 1600 kcmil aluminium/copper)1
	AWG 1250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Wiring configuration	3-wire
Phase connection	ABC
Maximum Height	11 in (279.40 mm)
Maximum Width	6 in (152.40 mm)
Maximum Depth	5.84 in (148.34 mm)
Tightening torque	115.06 Lbf.In (13 N.m) 0.070.47 in² (42304 mm²) AWG 1600 kcmil)
	115.06 lbf.in (13 N.m) 0.070.20 in² (42127 mm²) AWG 1250 kcmil)

Environment

Product certifications	UL Listed CSA

Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901426325
Nbr. of units in pkg.	1
Package weight(Lbs)	18.34 lb(US) (8.32 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.00 in (22.86 cm)
Package 1 width	11.70 in (29.718 cm)
Package 1 Length	17.50 in (44.45 cm)

Offer Sustainability

Onor Gastamasinty	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months