




LXEN



LXEM



LXEW

XE Family LED Enclosed & Gasketed Luminaires

A full family of LED linear enclosed and gasketed luminaires for rough service applications

	LXEN	LXEM	LXEW
	Narrow 4' housing fits easily into confined spaces	Mid-size and mainstream, offering the widest selection of options	An enclosed highbay/lowbay for demanding areas
Width	4"	6 ⁷ / ₈ "	15"
Available Lengths	4'	2', 4', 8'	4'
IP65	✓	✓	✓
IP66 with standard latches	✓	✓	✓
IP67	✓	4', 8'	✓
Wet Label	✓	✓	✓
F1 Weatherability (UV resistance)	✓	✓	✓
UL Sanitation to NSF Standards	✓	✓	✓
Lumen Packages	2,000 – 4,300	3,150– 22,473	11,079 – 38,228
Fluorescent Replacement	1-T8, 2-T8, 1-T5HO	2-T8, 3-T8, 4-T8, 2-T5HO, 4-T5HO	4T-8, 6-T8, 8-T8, 4-T5HO, 6-T5HO, 8-T5HO

LXEN - [] - [] - [] - [] - []

MODEL	SIZE	COLOR TEMP	SHIELDING	DRIVER	VOLTAGE	OPTIONS
LXEN LED Narrow Enclosed and Gasketed	4 4'	30 3000K 35 3500K 40 4000K 50 5000K	RFA Ribbed Frosted Acrylic ¹	E Fixed Output ED 0-10V Dimming	U 120V- 277V	GLR Fast Blow Fuse SSL Stainless Steel Tamper Resistant Ready Latches TP Tamper Proof Latches F3C8W 3 Wire 8' Wet Cord F3C15W 3 Wire 15' Wet Cord SWH Single Wet Hub 1/2" NPT Hub DWH Dual Wet Hub 1/2" NPT Hub HT Elevated Ambient ^{1,4}

ACCESSORIES (Order Separately)

XEHC Chain Hanger Kit (Includes 14" Chain)

XE45MB 45° Mounting Bracket

XE45MBSS 45° Stainless Steel Mounting Bracket

LUMEN OUTPUT

XW Extra Low Watt
LW Low Watt

LXEN PRODUCT AVAILABILITY			
Length	XW	LW	Efficacy Up To
4'	2,000 - 2,200	3,800 - 4,300	122

Nominal lumen range represents 3000K through 5000K. Lumens vary according to color temperatures and other factors. See specific photometric test(s).

LXEM - [] - [] - [] - [] - [] - []

MODEL	SIZE	COLOR TEMP	SHIELDING	DRIVER	VOLTAGE	OPTIONS
LXEM LED Enclosed & Gasketed	2 2' ^{1,2,3,4} 4 4' 8 8'	30 3000K 35 3500K 40 4000K 50 5000K	RFA Ribbed Frosted Acrylic RA Ribbed Clear Acrylic DFA Deep Frosted Acrylic DCA Deep Clear Acrylic RFP Ribbed Frosted Polycarbonate ⁵ RP Ribbed Clear Polycarbonate ⁵	E Fixed Output ESD Step Dimming ⁶ ED 0-10V Dimming ED1 0-10V 1% Dimming ⁶	U 120V- 277V 347 347V	GLR Fast Blow Fuse SSL Stainless Steel Tamper Resistant Ready Latches TP Tamper Proof Latches ELL14 Emergency Battery Pack Installed, 1400 Lumens ^{3,7} F3C8W 3 Wire 8' Wet Cord F3C15W 3 Wire 15' Wet Cord F4C8W 4 Wire 8' Wet Cord F4C15W 4 Wire 15' Wet Cord F5C8W 5 Wire 8' Wet Cord F5C15W 5 Wire 15' Wet Cord F6C6W 6 Wire 6' Wet Cord SWH Single Wet Hub 1/2" NPT Hub DWH Dual Wet Hub 1/2" NPT Hub ZRE ControlScope® compatible ^{7,9}

ACCESSORIES (ORDER SEPARATELY)

XEDPM Dual Pendant Brackets (pendant by others)⁸

XEHC Chain Hanger Kit (Includes 14" Chain)

XE45MB 45° Mounting Bracket¹⁰

XE45MBSS 45° Stainless Steel Mounting Bracket¹⁰

LUMEN OUTPUT

VW Very Low Watt
LW Low Watt
ML Medium Lumen
HL High Lumen
VL Very High Lumen
XL Xtra High Lumen²

SENSOR KITS (Order Separately)
All sensor kits include Occupancy & Daylight.
Daylight activation requires setting of dip-switches on site.

Catalog #	# Relays	Lens Type	Voltage	Wet Label
OS1360WLK	1	360°	120/277	Yes
OS2360WLK	2	360°	120/277	Yes
OS1AWLK	1	Aisle	120/277	Yes
OS2AWLK	2	Aisle	120/277	Yes

¹ VL and XL not available in 2' size.
² Not available with battery pack.
³ Not available with XL lumen package.
⁴ Not available with VL lumen package.
⁵ 2' and 4' only. 8' not available.
⁶ See table spec sheet for availability
⁷ Not available in 347V
⁸ Requires 3/8" OD threaded rod by others.
⁹ Registered trademark of Daintree Networks, used by permission.
¹⁰ 2 required for 8' fixture

LXEM PRODUCT AVAILABILITY						
Length	VW	LW	ML	HL	VL	XL
2'	2,145 - 2,708	2,738 - 3,529	3,862 - 4,921	4,254 - 5,416	-	-
4'	2,802 - 3,433	3,726 - 4,922	4,533 - 5,646	5,449 - 6,763	7,086 - 8,415	9,059 - 11,237
8'	6,078 - 6,866	8,095 - 9,276	9,844 - 11,293	11,851 - 13,525	14,747 - 16,830	19,558 - 22,473

Lumens vary according to color temperatures and other factors. See specific photometric test(s).

LXEW - [] - [] - [] - [] - [] - []

MODEL	SIZE	LUMEN OUTPUT	LENS	DRIVER	OPTIONS
LXEW Industrial Enclosed & Gasketed LED High Bay	4 4'	L Low Watt M Medium Lumen MH Medium High Lumen H High Lumen HV High Very High Lumen V Very High Lumen X Extra High Lumen	FA Frost Impact Resistant Acrylic (std.) CA Clear Impact Resistant Acrylic CP Clear UV Stabilized Polycarbonate	E Fixed Output ED 0-10V Dimming	GLR Fast Blow Fuse SSL Stainless Steel Tamper Resistant Ready Latches TP Tamper Proof Latches ELL14 Emergency Battery Pack Installed, 1400 Lumens ^{2,3} F3C8W 3 Wire 8' Wet Cord F3C15W 3 Wire 15' Wet Cord F4C8W 4 Wire 8' Wet Cord F4C15W 4 Wire 15' Wet Cord F5C8W 5 Wire 8' Wet Cord F5C15W 5 Wire 15' Wet Cord F6C6W 6 Wire 6' Wet Cord SWH Single Wet Hub 1/2" NPT Hub DWH Dual Wet Hub 1/2" NPT Hub

ACCESSORIES (ORDER SEPARATELY)

LHVQM5 Aircraft Cable, 5' (Pair)

LHVQM10 Aircraft Cable, 10' (Pair)

XEWMHSS Mounting Strap Hardware Kit, Stainless Steel

XEWRBSZN Rigid Surface Mounting Bracket Kit, Zinc Plate

XEWRBSBS Rigid Surface Mounting Bracket Kit, Stainless Steel

XEWFBSBS Surface Mounting Bracket Kit, Stainless Steel

¹ Not available with V and X packages
² Not Available with 347v/480v
³ Not Available with HV, V, X lumen packages

LXEW PRODUCT AVAILABILITY							
Length	L	M	MH	H	HV	V	X
4'	11,079 - 12,495	15,349 - 16,539	16,580 - 18,689	20,714 - 22,321	23,805 - 25,651	29,040 - 32,557	35,357 - 38,099

Lumens vary according to color temperatures and other factors. See specific photometric test(s).

