

Main

Product	Secondary surge arrester
Range	Surge Breaker QO

Complementary

Complementary		
Surge Current	22.5 kA	
Voltage Rating	120/240 V AC	
Number of Phases	1 phase	
Wiring Configuration	3-wire	
MCOV	150 V 300 V	
SCCR	22 kA	
Local Signalling	1 LED green normal operation	
Product destination	Load center QO	
Height	3.7 in (93.98 mm)	
Width	1.5 in (38.10 mm)	
Depth	2.6 in (66.04 mm)	

Environment

Enclosure Rating	NEMA 2
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI	
Discount Schedule	DE1B	
GTIN	00785901210894	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.65 lb(US) (0.29 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Package 1 Height	1.70 in (4.318 cm)
Package 1 width	3.00 in (7.620 cm)
Package 1 Length	5.50 in (13.970 cm)

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☐ China RoHS Declaration	

Contractual warranty

Warranty 18 months		
	vvarranty	To monate

Approximate Dimensions

