



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Thermal-magnetic
Breaking capacity code	D

Complementary

Line Rated Current	150 A
Number of Poles	3P
Interrupt Rating	25 KA 240 V AC 18 KA 480 V AC 14 KA 600 V AC 20 kA 250 V DC
[Ue] rated operational voltage	250 V DC 600 V AC
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Phase	ABC
Magnetic hold current	900 A
Magnetic tripping current	1700 A
Maximum Height	9.73 in (247.14 mm)
Maximum Width	4.48 in (113.79 mm)
Maximum Depth	4.8 in (121.92 mm)
Tightening torque	44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0

Environment

Product certifications	UL Listed CE CSA IEC
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01112 - HD, JD I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901420002
Nbr. of units in pkg.	1
Package weight(Lbs)	5.98 lb(US) (2.71 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.60 in (14.224 cm)
Package 1 width	8.60 in (21.844 cm)
Package 1 Length	15.00 in (38.1 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------